

BASF SONOGUARD

Estimating Worksheet Only - Call to Confirm Prices
Update: June, 09

| PRODUCT | ESTIMATED COVERAGE |
|--|---|
| Sonoguard Base Coat Slope Grade | 60 sq. ft./gallon 5-gl pail = 300 sq. ft. |
| Sonoguard Base Coat Self-Leveling | Same as above |
| | |
| Sonoguard Top Coat Pre-tinted colors: Gray, Charcoal Gray, Tan | Light to Medium Duty 60 sq. ft./gal (25 wet mils) Back roll sand into top coat Heavy Duty (2 top coats) 80 sq. ft./gal. (20 wet mils) Back roll & apply sand 80 sq. ft./gal 2 nd coat (2 nd coat) |
| Sonoguard Top Coat Tint Base (40 Standard Color paks) | Coverage same as pre-tinted colors above |
| Sonoguard Color Paks | 2 ea. per 5-gallon pail Top Coat |
| | |
| Primer | Not required unless specified |
| | |
| Accessories | |
| Caulking for joints, NP1 | 10 oz. cartridge (30/case) |
| Deck Seam Tape | 4" x 180 lin. ft. |
| Sand, 100 lb. bags #20 | 10-25 lb./100 sf Lt. Duty 50-60 lb./100 sf Hvy Duty |